

Dynamic 2100

Battery powered plastic strapping tool



**Versatile and user-friendly strapping tool
for most applications in all industrial sectors.**

Dynamic 2100

Characteristics

Strapping qualities:	PET (Polyester) and PP (Polypropylene) plain or embossed
Strapping dimensions:	widths 12.7 - 19.0mm / 1/2 - 3/4 "
	thicknesses 0.40 - 1.27mm / .016 - .050 "
Weight:	4.3 kg / 9.5 lbs
Average seal strength:	approx. 75 %
Sealing method:	Friction weld
Tensioning force:	650 - 3000 N / 146 - 675 lbs adjustable
Tensioning speed:	160 - 230 mm/s / 6.3 - 9 inch/sec.
Power supply:	Li-Ion battery 14.4 VDC / 3 Ah

Dynamic 2100



Advantages:

- Light and versatile strapping tool
- Robust and durable design
- Well proven strapping technology
- Simple one-handed operation
- Excellent cost - performance ratio
- Latest Li-Ion battery technology



Item No.	Model	Strap width		Strap thicknesses	
		mm	inch	mm	inch
43.3291	DYNAMIC 2100/12.7/0.40-0.64	12.7	1/2"	0.40-0.64	.016-.025
43.3292	DYNAMIC 2100/12.7/0.65-1.05	12.7	1/2"	0.65-1.05	.026-.041
43.3301	DYNAMIC 2100/13/0.40-0.64	13		0.40-0.64	.016-.025
43.3302	DYNAMIC 2100/13/0.65-1.05	13		0.65-1.05	.026-.041
43.3311	DYNAMIC 2100/16/0.40-0.64	16	5/8"	0.40-0.64	.016-.025
43.3312	DYNAMIC 2100/16/0.65-1.05	16	5/8"	0.65-1.05	.026-.041
43.3322	DYNAMIC 2100/19/0.65-1.05	19.0	3/4"	0.65-1.05	.026-.041
43.3323	DYNAMIC 2100/19/1.06-1.27	19.0	3/4"	1.06-1.27	.042-.050

SEARO
Strapping Systems

西域包裝科技有限公司

SEARO PACKAGING CO.,LTD

高雄市美濃區泰安路353號

NO. 353, TAI-AN RD., MEINONG DIST., TAIWAN

TEL: 886-7-6812225 FAX: 886-7-6812225